

PRODUCT INFORMATION

- Insert coat made of boiler steel, with thickness of 3 mm, P265GH grade in accordance with EN 10028-2
- Steel doors made of special profile, guaranteeing rigidity and high-temperature resistance.
- Heat-resistant ceramic glass with working temperatures of up to 800 °C.
- Steel base of insert fitted with an intake throttle of outside cold air.
- Insert equipped with air curtain, to guarantee the maintenance of a substantially pure glass effect.
- Specially designed rear part of the body, designed for secondary air supply to the upper part of the furnace. Allows to increase the efficiency of the device by after-burning the exhaust fumes.

LEFT-SIDED HORIZONTAL FIREPLACE INSERT WITH A GUILLOTINE DOOR **ALBERO AL16LG.H**

| | |
|---|--|
| Nominal power (kW) | 16 |
| Heating load range (kW) | 8-19 |
| Flue diameter (mm) | 200 |
| Heat performance (%) | 81,1 |
| CO emission (with 13% O ₂) | 0,061 |
| Dust emission (g/m ³) | 0,035 |
| Exhaust emission (°C) | 318 |
| Weight (kg) | 212 |
| Log maximum lenght (cm) | 40 |
| Material | boiler steel with thickness of 3 mm P265GH |
| Fuel Type | hardwood, briquettes, lignite |
| Min. Active field of exhaust grilles (cm ²) | 1000 |
| Min. Active field of intake grilles (cm ²) | 800 |
| Size of fireplace glass (mm) | 680 x 530 x 375 |

